

LT-2 WT-1B WT-2

Functions:

Ultra slim shell design, exquisite appearance, simultaneously display temperature and humidity. Max. Min temperature and humidity memory. Switch between °C and °F. Suitable for home and office.

Specification

Specification: 100×32×8.6(mm)

Technical parameters

- ◆ Power supply: DC3.0V, one button battery CR2032
- ◆ Measuring range: Temperature: -5°C ~ +50°C (23°F ~ 122°F)
Humidity: 30%RH ~ 90%RH
- ◆ Resolution: 1
- ◆ Accuracy: Temperature: ±1°C Humidity: ±5%RH



LT-2

Functions

Pencil-type, portable, lengthened metal probe, temperature memory, low power consumption, low battery indicating and sensor fault indicating, switch between °C/°F, widely applied to foodstuff industry.



WT-1B

Specification

Product size: Φ20×207 (mm)

Technical parameters

- ◆ Power: DC1.5V LR44 button battery
- ◆ Measuring range: -50°C ~ +300°C (-58°F ~ +572°F)
- ◆ Resolution: 1 (≥400°F), 0.1 at others
- ◆ Accuracy: ±1°C (-20°C ~ +80°C); ±5°C for other range



Functions:

Fashionable appearance, lengthened metal probe with lead wire, data keeping, switch between °C/°F, Max./Min. temperature memory, temperature upper and lower limit setting and exceeding temperature alarming, widely applied to HVAC and foodstuff industry.

Specification

Product size: 59×105×19(mm)

Technical parameters

- ◆ Power: DC1.5V 7#alkaline battery (optional)
- ◆ Measuring range: -50°C ~ +300°C (-58°F ~ +572°F)
- ◆ Resolution: 0.1 (-19.9°C ~ 199.9°C), 1 at others
- ◆ Accuracy: ±1°C (-20°C ~ +80°C), ±5°C at others



WT-2

