

MORE HEAT, CONTROL AND CONSISTENCY



3800°

3600°

3400°.

.....

-

3000° -

800° –

\_

2600° -

\_\_\_\_\_

2400° -

.

200°

000°

enno

. . . . .

1-100 -

200°.

1000°



# HARRIS AIR-FUEL HAND TORCHES FOR DEMANDING PROFESSIONALS

The new line of Harris air-fuel hand torches brings high performance and convenience to professional heating, ventilation, air conditioning, plumbing and refrigeration contractors. Built with heating performance, temperature consistency and flame control in mind, a Harris hand torch is the perfect partner for demanding brazing and soldering applications.





#### HSLT604HD TIP DETAIL

### **HOT TECHNOLOGY**

Professional contractors need high-performance torches with truly hot flames engineered to deliver faster brazing and soldering times. Harris hand torches incorporate specially designed high-output swirl combustion tips that are tested for optimal brazing and soldering performance. When it's time to work, have the power of a Harris torch in your hand ... and get the job done right.

## **DURABLE MATERIALS**

HSLT604

BRASS

STAINLESS

ALUMINUM

CARBIDES

COPPER

Harris hand torches are constructed to stand up in the harshest situations. With industrial grade materials like 304 stainless steel and 360 brass, Harris hand torches mean business. In fact, our hand torches are individually tested for quality and performance. With Harris, you get a high degree of durability and reliability in every hand torch.

### VERSATILE PERFORMANCE

Harris hand torches have the heating performance and temperature consistency needed for many of today's common brazing and soldering situations. And, with precise flame controls, professional contractors can easily get dialed in for a wide range of applications. With a Harris hand torch, professional contractors are set up to deliver.



6 - 25 mm

HARRIS



13 – 51 mm

Propane tanks.

See back cover for details.



Harris offers a full line of air-fuel hand torches for all of your brazing and soldering needs.



MODEL	STYLE	MAP-Pro™		PROPANE	
		SOLDERING CAPACITY	BRAZING CAPACITY	SOLDERING CAPACITY	BRAZING CAPACITY
HSLT604HD	Trigger Torch -	3/4"-4"	1/4"-1 1/4"	3/4"-3"	1/4"-1"
P/N 1400351	Heavy Duty	20 – 102 mm	6 – 32 mm	20 – 76 mm	6 – 25 mm
HSLT604	Trigger Torch	1/8" - 3"	1/16" - 1"	1/8"-2"	1/16"-3/4"
P/N 1400350		3 – 76 mm	1.6 – 25 mm	3 – 51 mm	1.6 – 20 mm
HTS99	Auto Ignite	1/4"-3"	1/4"-1 3/4"	1/4"-3"	1/4"-1"
P/N 1400354		6 – 76 mm	6 – 45 mm	6 – 76 mm	6 – 25 mm
HTM9	Manual Lighting	1/4"-3"	1/4"-1 3/4"	1/4"-3"	1/4"-1"
P/N 1400352		6 – 76 mm	6 – 45 mm	6 – 76 mm	6 – 25 mm
HTM11	Manual Lighting	3/4"-4"	1/2"-2"	3/4"-3 1/2"	1/2"-2"
P/N 1400353		20 – 102 mm	13 – 51 mm	20 – 90 mm	13 – 51 mm

ITEM	DESCRIPTION	UNITS PER CASE	CASES PER PALLET
MAP-Pro <sup>TM</sup> P/N 4300672	14.1 oz. MAP-Pro™	12	90
Propane P/N 4300675	14.1 oz. Propane	12	90

MAP//Pro™ is a registered trademark of Worthington Industries.



ORDERING INFORMATION 800.733.4533 LEARN MORE www.harrisproductsgroup.com

