

Honeywell Genetron® Refrigerants



Refrigerants with the future in mind

Honeywell

Genetron Refrigerants

A world leader in the invention, manufacture and supply of environmentally safer refrigerants

Honeywell's Genetron Refrigerants

In these changing times, it's important to have a knowledgeable refrigerant partner that can help your business make the transition to environmentally safer hydrofluorocarbon products. Honeywell strives to be that full-service supplier by providing products and support programs that meet the changing needs of air conditioning and refrigeration professionals. The broad product line we offer features Genetron brand solutions for virtually every application in air conditioning and refrigeration.

Technical Support

Honeywell's Genetron refrigerants are brought to you by some of the most knowledgeable people in the industry. These engineers and specialists work with the leading equipment and compressor manufacturers to guarantee that Genetron refrigerants will meet your needs today and in the future. Honeywell also serves as a valuable information resource to the industry by offering a full complement of informational materials, ranging from technical bulletins and retrofit guidelines to in-field presentations made by our sales and technical professionals.

Air Conditioning

A variety of environmentally safer alternatives are available from Honeywell for the air conditioning industry. For the unitary-air-conditioning market, we offer non-ozone-depleting replacements for R-22, including Genetron 407C and Genetron AZ-20® (R-410A). R-410A is an azeotrope-like mixture of HFC-32 and HFC-125 that was invented and patented by Honeywell. Our AZ-20 brand of R-410A has been selected by equipment manufacturers as the refrigerant of choice for providing non-ozone-depleting air conditioning and heat pump options to homeowners.

Our alternative refrigerants for centrifugal chillers include Genetron 123, 245fa, and 134a. Genetron 245fa is a non-ozone depleting fluid developed by Honeywell for use in centrifugal chillers. Genetron AZ-50® (R-507) and AZ-20 are available for positive displacement chiller applications.

As a major supplier to the world's leading automobile and truck manufacturers, we offer a non-ozone-depleting refrigerant, Genetron 134a, for mobile air conditioning systems. As an aid to automotive mechanics worldwide, we offer Genetron 134aUV — a mixture of Genetron 134a and a refrigerant-soluble dye that fluoresces when viewed under ultraviolet light. This novel solution now makes it easier, cleaner, and less expensive to pinpoint leaks in automotive air conditioning systems.

Refrigeration

The flagship of Honeywell's R-22 replacements is Genetron® Performax™ LT. Genetron Performax LT is a low toxicity, non-flammable replacement for R-22 suitable for both refrigeration system retrofits and new installations. Genetron Performax LT is a close capacity match to R-22 in both medium- and low- temperature applications. The efficiency of Genetron Performax LT is highest among currently available replacements hence it contributes to low operating costs. Because no TXV changes or adjustments are needed, retrofit costs are low. The global warming potential of Performax LT is lower than comparable products.

Honeywell offers a broad line of R-502 and R-22 replacements for low- and medium-temperature refrigeration systems. A popular alternative is Genetron AZ-50® (R-507), an azeotropic HFC mixture

of R-125 and R-143a invented and patented by Honeywell. R-507 can be used in both low- and medium-temperature refrigeration systems, and in both new equipment and retrofit applications. Sold under our brand name AZ-50, R-507 has been approved by the world's leading refrigeration manufacturers. It is used worldwide in supermarkets and in industrial, food-service, and other applications.

Another alternative to R-502 and R-22 is Genetron 404A, which is used in both low- and medium-temperature systems. Genetron HP80 and Genetron 408A are also excellent interim products for low- and medium-temperature applications.

For medium-temperature systems, we manufacture interim products such as Genetron MP39, Genetron MP66 and Genetron 409A for retrofitting applications. We also offer Genetron 134a as a long-term non-ozone-depleting solution for new and retrofit medium-temperature refrigeration systems.

Retrofitting

Retrofitting existing refrigeration systems to environmentally safer refrigerants plays a major role in the industry's move away from ozone depleting substances. Honeywell encourages its customers to retrofit systems now to help guarantee their smooth and economical operation over the long term.

Comprehensive information is available to help retrofit refrigeration systems to all of our alternative refrigerants.

Reclamation

As a responsible chemical producer, Honeywell discourages any unnecessary release of refrigerants to the atmosphere and encourages contractors and end-users to return used refrigerant for reclamation and eventual re-use. Honeywell offers an economical refrigerant reclamation program through our network of wholesalers and distributors.

Technical Expertise

An integral part of Honeywell's investment in non-ozone-depleting fluorocarbon products is the company's Fluorine Products Technology Center in Buffalo, N.Y. This world-class research facility plays a leading role in our application support programs for customers. Some of the work performed at the center includes materials compatibility, lubricant miscibility and system performance testing.



Genetron Refrigerants Products Guide



HCFC

Dichlorotrifluoroethane (CHCl₂CF₃)
A very low ozone depleting compound that serves as a replacement for CFC-11 in centrifugal chillers.



HFC

Pentafluoropropane (CF₃CH₂CHF₂)
A non-ozone depleting candidate replacement for CFC-11 in centrifugal chillers.



HCFC

Chlorotetrafluoroethane (CHClCF₃)
A medium pressure refrigerant for chiller applications.



HFC

Tetrafluoroethane (CF₃CH₂F)
Replaces CFC-12 in auto air conditioning and in residential, commercial and industrial refrigeration systems.

Selected Physical Data

123

245fa

124

134a

Substitutes (See Legend Below)	■	■	□	
ASHRAE Number	R-123	R-245fa	R-124	R-134a
Molecular Weight	152.9	134.0	136.5	102.0
Boiling Point @ 1 Atm,* (°F)	82.1	59.3	10.5	-14.9
Freezing Point @ 1 Atm, (°F) [Pure Fluids*]	-160.9	-151.8	-326.5	-153.9
Critical Temperature* (°F)	362.6	309.2	252.1	213.9
Critical Pressure* (psia)	531.1	529.5	525.7	588.8
Saturated Liquid Density @ 86°F,* (lb/ft ³)	90.6	82.7	83.5	74.1
Specific Heat of Liquid @ 86°F,* (Btu/lb •°F)	0.25	0.32	0.27	0.35
Specific Heat of Vapor @ Constant Pressure* (Cp), @ 86°F and 1 Atm, (Btu/lb •°F)	0.17	0.22	0.18	0.21
Flammable range, (Based on ASHRAE Standard 34 with Match Ignition)††	None	None	None	None
ANSI/ASHRAE Standard 34-1992 Safety Group Classification	B1	A1	N.C.†††	A1

Legend:

- CFC 11 Substitutes
- CFC 12 Substitutes
- R-502 Substitutes
- CFC 13/R-503 Substitutes
- HCFC 22 Substitutes

Refrigerants are listed in highest-to-lowest order according to their boiling point at 1 atmosphere pressure.



Blend

Pentafluoroethane Tetrafluoroethane Isobutane (CF₃CHF₂/CF₃CH₂F/(CH₃)₂CH)
A non-ozone-depleting replacement for HCFC-22 in low- and medium-temperature commercial refrigeration systems.



Blend

Difluoromethane Pentafluoroethane Tetrafluoroethane (CH₂F₂/CF₃CHF₂/CF₃CH₂F)
A non-ozone-depleting replacement for HCFC-22 in various air-conditioning applications, as well as in positive displacement refrigeration systems.



Blend

Pentafluoroethane Trifluoroethane Chlorodifluoromethane (CF₃CHF₂/CF₃CH₃/CHClF₂)
An interim replacement for retrofitting low- and medium-temperature commercial refrigeration systems.



Blend

Difluoromethane Pentafluoroethane Tetrafluoroethane (CH₂F₂/CF₃CHF₂/CF₃CH₂F)
Well-matched performer as a non-ozone depleting replacement for R-22 in low- and medium-temperature commercial refrigeration systems.

Selected Physical Data

422D

407C

408A

Performax™ LT

Substitutes (See Legend Above)	■	■	■	■
ASHRAE Number	R-422D	R-407C	R-408A	R-407F
Molecular Weight	109.9	86.2	87.7	82.1
Boiling Point @ 1 Atm, (°F)	-45.8 ^Ω	-46.5 ^Ω	-48.3 ^Ω	-50.9
Freezing Point @ 1Atm, (°F)	—	-256.0	—	—
Critical Temperature* (°F)	175.2	186.9	181.7	180.8
Critical Pressure* (psia)	566.4	671.4	622.9	689.6
Saturated Liquid Density @ 86°F, (lb/ft ³)	69.9	69.6	64.8	68.3
Specific Heat of Liquid @ 86°F (Btu/lb •°F)	0.35	0.38	0.35	0.39
Specific Heat of Vapor @ Constant Pressure* (Cp), @ 86°F and 1 Atm, (Btu/lb •°F)	0.20	0.20	0.19	0.2
Flammable range, (Based on ASHRAE Standard 34 with Match Ignition)††	None	None	None	None
ANSI/ASHRAE Standard 34-1992 Safety Group Classification	A1	A1	A1	A1

* NIST REFPROP 8, unless noted otherwise

^Ω Bubble point temperature.

† Upper and lower vapor flammability (Vol.%).

†† ASTM E681-85 match ignition ambient conditions.

††† N.C. Not Classified.

Ω @ -30°F.

Contains HFC-125/
HFC-134a/HC-600a

Contains HFC-32/
HFC-125/HFC-134a

Contains HFC-125/
HFC-143a/HCFC-22

Contains HFC-32/
HFC-125/HFC-134a



Blend

Chlorodifluoromethane
Difluoroethane
Chlorotetrafluoroethane
(CHClF₂/CHF₂CH₃/CHClFCF₃)
An interim replacement for CFC-12 in medium-temperature commercial refrigeration systems.

MP39



R-401A
94.4
-27.3°
—
225.2
668.3
73.1
0.31
0.18
None
A1

Contains HCFC-22/
HFC-152a/HCFC-124.



Blend

Chlorodifluoromethane
Difluoroethane
Chlorotetrafluoroethane
(CHClF₂/CHF₂CH₃/CHClFCF₃)
An interim replacement for CFC-12 in low-temperature commercial refrigeration systems.

MP66



R-401B
92.9
-30.2°
—
222.0
679.6
76.7
0.30
0.17
None
A1

Contains HCFC-22/
HFC-152a/HCFC-124.



Blend

Chlorodifluoromethane
Chlorotetrafluoroethane
Chlorodifluoroethane
(CHClF₂/CHClFCF₃/CClF₂CH₃)
An interim replacement for CFC-12 in refrigeration systems.

409A



R-409A
97.4
-30.0°
—
228.7
681.5
74.6
0.30
0.17
None
A1

Contains HCFC-22/
HCFC-124/ HCFC-142b.



HCFC

Chlorodifluoromethane
(CHClF₂)
As a refrigerant, operates with higher system pressures but low compressor displacement. Popular in residential, commercial and industrial applications.

22



R-22
86.5
-41.5
-251.4
205.1
723.7
73.1
0.31
0.16
None
A1



Blend

Pentafluoroethane
Trifluoroethane
Tetrafluoroethane
(CF₃CHF₂/CF₃CH₃/CF₃CH₂F)
A long-term, non-ozone-depleting replacement for R-502 in low- and medium-temperature commercial refrigeration systems.

404A



R-404A
97.6
-51.2°
—
161.7
540.8
63.6
0.38
0.21
None
A1

Contains HFC-125/
HFC-143a/HFC-134a.



Azeotrope

Pentafluoroethane
Trifluoroethane
(CF₃CHF₂/CF₃CH₃)
A non-ozone depleting azeotropic mixture of HFC-125 and HFC-143a. It has been primarily designed to replace R-502 in low- and medium-temperature commercial refrigeration applications such as supermarket display cases and ice machines.

AZ-50[®] 507



R-507, R-507A
98.9
-52.2°
-178.0
159.1
537.4
63.8
0.38
0.21
None
A1

Contains HCFC-22/
HFC-125/HC-290



Blend

Chlorodifluoromethane
Pentafluoroethane
Propane
(CHClF₂/CF₃CHF₂/C₃H₈)
An interim replacement for R-502 used mainly for ice machines and soft ice cream machines.

HP81



R-402B
94.7
-52.7
—
181.2
654.9
70.4
0.33
0.18
None
A1

Contains HFC-125/HFC-143a.



Blend

Chlorodifluoromethane
Pentafluoroethane
Propane
(CHClF₂/CF₃CHF₂/C₃H₈)
An interim replacement for retrofitting low- and medium-temperature commercial refrigeration systems.

HP80



R-402A
101.6
-56.1°
-153.0
168.5
612.0
70.0
0.34
0.18
None
A1

Contains HCFC-22/
HFC-125/HC-290.



Azeotropic Mixture

Difluoromethane
Pentafluoroethane
(CH₂F₂/CF₃CHF₂)
Widely accepted to replace HCFC-22 in air conditioning and refrigeration applications.

AZ-20[®] 410A



R-410A
72.6
-60.6
-247.0
160.4
711.0
64.5
0.42
0.20
None
A1

Contains HFC-32/HFC-125.



HFC

Trifluoromethane
(CHF₃)
A specialty low temperature refrigerant that may be used to replace CFC-13 and R-503 in the low stage of cascade systems.

23



R-23
70.0
-115.6
-247.2
79.1
700.8
77.6 Ω
0.34 Ω
0.16 Ω
None
N.C.†††

Contains HFC-23/FC-116.



Azeotrope

Trifluoromethane
Hexafluoroethane
(CHF₃/C₂F₆)
A non-ozone depleting azeotrope of HFC-23 and FC-116 used to replace CFC-13 and R-503 in the low stage of cascade systems.

508B



R-508B
95.4
-125.7
—
52.2
547.0
78.8 Ω
0.31 Ω
0.16 Ω
None
A1

Contains HFC-23/FC-116.

Vapor Pressures

Temp °F	124		134a		MP39		MP39		MP66		MP66		409A		409A		22	422 D		422 D		407C		407C		408A		408A		Performax Lt		404A		404A		AZ-50®	507A		HP81		HP81		HP80		HP80		AZ-20®	410A	
	(liq)	(vap)	(liq)	(vap)	(liq)	(vap)	(liq)	(vap)	(liq)	(vap)	(liq)	(vap)	(liq)	(vap)	(liq)	(vap)	(liq)	(vap)	(liq)	(vap)	(liq)	(vap)	(liq)	(vap)	(liq)	(vap)	(liq)	(vap)	(liq)	(vap)	(liq)	(vap)	(liq)	(vap)	(liq)	(vap)	(liq)	(vap)	(liq)	(vap)	(liq)	(vap)	(liq)	(vap)					
-40	22.1*	14.8*	8.4*	13.8*	6.7*	12.4*	6.7*	14.8*	0.6	2.4	2.3*	2.7	4.6*	3.5	3.1	4.9	0.5	4.9	4.3	5.4	5.6	3.7	7.4	5.7	10.8																								
-35	20.9*	12.5*	5.3*	11.4*	3.4*	9.7*	3.5*	12.5*	2.6	4.6	0.8	5.1	0.9*	5.8	5.5	7.5	1.9	7.5	6.8	8.1	8.2	6.2	10.3	8.4	14.1																								
-30	19.4*	9.8*	2.0*	8.7*	0.1	6.8*	0.0	9.9*	4.9	7.1	3.0	7.7	1.6	8.5	8.0	10.4	4.2	10.3	9.6	11.0	11.1	8.9	13.4	11.4	17.8																								
-25	17.8*	6.9*	0.8	5.6*	2.0	3.5*	1.9	7.0*	7.4	9.9	5.4	10.6	3.9	11.3	10.9	13.6	6.8	13.4	12.7	14.1	14.2	11.9	16.8	14.6	21.9																								
-20	16.0*	3.7*	2.9	2.2*	4.1	0.1	4.0	3.8*	10.2	12.9	8.1	13.7	6.5	14.5	14.0	17.1	9.7	16.8	16.0	17.6	17.7	15.1	20.5	18.2	26.3																								
-15	14.0*	0.1*	5.1	0.7	6.5	2.0	6.3	0.2*	13.2	16.2	11.0	17.2	9.3	17.9	17.4	20.9	12.9	20.5	19.7	21.4	21.4	18.7	24.5	22.5	31.2																								
-10	11.8*	1.9	7.5	2.8	9.1	4.2	8.8	1.8	16.5	19.8	14.3	20.9	12.3	21.7	21.1	25.1	16.4	24.6	23.6	25.5	25.5	22.6	28.8	26.3	36.5																								
-5	9.3*	4.1	10.1	5.0	11.9	6.6	11.6	4.0	20.1	23.7	17.8	25.0	15.7	25.7	25.1	29.6	20.2	28.9	27.9	30.0	29.9	26.8	33.6	30.8	42.2																								
0	6.6*	6.5	13.0	7.4	14.9	9.2	14.6	6.3	24.0	27.9	21.7	29.5	19.4	30.1	29.5	34.5	24.4	33.7	32.6	34.8	34.6	31.4	38.7	35.8	48.4																								
5	3.6*	9.1	16.1	10.1	18.2	12.1	17.8	8.8	28.3	32.5	25.8	34.3	23.5	34.9	34.2	39.8	28.9	38.8	37.7	40.1	39.8	36.3	44.2	41.2	55.2																								
10	0.3*	11.9	19.5	13.0	21.8	15.2	21.3	11.6	32.8	37.5	30.4	39.5	27.9	40.0	39.3	45.6	33.9	44.3	43.1	45.7	45.3	41.6	50.2	46.9	62.4																								
15	1.6	15.0	23.1	16.2	25.7	18.6	25.1	14.7	37.8	42.8	35.3	45.2	32.7	45.5	44.8	51.8	39.3	50.2	49.0	51.8	51.3	47.4	56.5	53.2	70.3																								
20	3.6	18.4	27.1	19.6	29.9	22.3	29.2	18.0	43.1	48.5	40.7	51.2	37.9	51.5	50.7	58.5	45.1	56.6	55.3	58.3	57.7	53.6	63.4	59.8	78.7																								
25	5.7	22.1	31.4	23.4	34.4	26.3	33.6	21.6	48.8	54.7	46.4	57.7	43.5	57.8	57.0	65.6	51.4	63.4	62.1	65.3	64.5	60.2	70.7	67.0	87.7																								
30	8.0	26.1	36.0	27.4	39.3	30.6	38.4	25.5	55.0	61.3	52.6	64.7	49.6	64.6	63.7	73.3	58.2	70.7	69.3	72.7	71.8	67.3	78.6	74.7	97.4																								
35	10.5	30.4	40.9	31.8	44.5	35.2	43.4	29.7	61.5	68.4	59.3	72.2	56.1	71.9	71.0	81.5	65.5	78.6	77.1	80.7	79.7	75.0	86.9	82.9	107.7																								
40	13.2	35.0	46.2	36.5	50.1	40.2	48.9	34.2	68.6	75.9	66.4	80.2	63.2	79.7	78.7	90.3	73.4	86.9	85.4	89.3	88.0	83.1	95.8	91.6	118.8																								
45	16.1	40.1	51.8	41.6	56.0	45.6	54.7	39.1	76.1	84.0	74.0	88.8	70.7	88.0	87.0	99.7	81.8	95.8	94.2	98.3	96.9	91.7	105.3	100.9	130.6																								
50	19.3	45.4	57.9	47.0	62.4	51.4	60.9	44.3	84.1	92.6	82.2	97.9	78.8	96.8	95.7	109.7	90.8	105.3	103.6	108.0	106.3	101.0	115.4	110.9	143.2																								
55	22.7	51.2	64.3	52.8	69.2	57.5	67.5	49.9	92.6	101.7	90.9	107.6	87.5	106.2	105.1	120.4	100.5	115.3	113.6	118.3	116.3	110.8	126.1	121.4	156.5																								
60	26.3	57.4	71.2	59.0	76.5	64.1	74.5	55.9	101.6	111.4	100.2	117.9	96.8	116.1	115.0	131.7	110.8	126.0	124.2	129.2	127.0	121.2	137.4	132.6	170.7																								
65	30.2	64.0	78.5	65.7	84.2	71.2	81.9	62.3	111.2	121.7	110.1	128.9	106.7	126.7	125.5	143.7	121.8	137.3	135.5	140.8	138.2	132.2	149.4	144.4	185.8																								
70	34.4	71.1	86.3	72.8	92.3	78.7	89.8	69.2	121.4	132.6	120.7	140.5	117.3	137.8	136.6	156.4	133.5	149.3	147.4	153.0	150.1	143.9	162.1	157.0	201.8																								
75	38.9	78.7	94.5	80.3	101.0	86.7	98.2	76.4	132.2	144.1	131.8	152.8	128.6	149.6	148.3	169.9	146.0	162.0	160.1	165.9	162.7	156.3	175.5	170.2	218.7																								
80	43.7	86.7	103.2	88.4	110.1	95.2	107.0	84.2	143.6	156.3	143.7	165.8	140.5	162.1	160.8	184.1	159.2	175.4	173.4	179.6	176.0	169.4	189.7	184.2	236.5																								
85	48.8	95.2	112.4	96.9	119.8	104.2	116.4	92.5	155.7	169.2	156.2	179.6	153.2	175.3	173.9	199.1	173.3	189.5	187.5	194.1	190.0	183.2	204.6	199.0	255.4																								
90	54.3	104.3	122.2	106.0	130.1	113.8	126.2	101.2	168.4	182.8	169.5	194.1	166.7	189.2	187.7	215.0	188.2	204.5	202.4	209.3	204.7	197.8	220.3	214.6	275.4																								
95	60.1	113.9	132.5	115.6	140.9	123.9	136.6	110.5	181.8	197.1	183.6	209.4	181.0	203.8	202.3	231.7	203.9	220.2	218.1	225.4	220.2	213.1	236.8	231.0	296.4																								
100	66.2	124.2	143.3	125.7	152.3	134.7	147.6	120.3	195.9	212.2	198.4	225.5	196.1	219.2	217.6	249.3	220.6	236.8	234.6	242.3	236.5	229.2	254.2	248.3	318.6																								
105	72.7	135.0	154.8	136.5	164.3	146.0	159.1	130.7	210.8	228.0	214.0	242.4	212.1	235.3	233.8	267.8	238.3	254.2	252.1	260.1	253.7	246.2	272.5	266.5	341.9																								
110	79.6	146.4	166.8	147.8	176.9	158.0	171.2	141.7	226.4	244.7	230.5	260.3	229.0	252.3	250.7	287.2	256.9	272.5	270.4	278.8	271.7	264.1	291.6	285.6	366.4																								
115	86.9	158.4	179.4	159.8	190.1	170.6	183.9	153.3	242.8	262.3	247.9	279.0	246.9	270.2	268.6	307.6	279.6	291.8	289.6	298.5	290.5	282.8	311.8	305.7	392.3																								
120	94.6	171.2	192.7	172.4	204.0	183.9	197.2	165.6	260.0	280.7	266.3	298.6	265.8	288.9	287.3	329.0	297.4	312.1	309.9	319.2	310.3	302.5	332.9	326.7	419.4																								
125	102.8	184.6	206.6	185.7	218.6	197.9	211.1	178.5	278.0	300.0	285.5	319.2	285.7	308.6	306.9	351.5	319.3	333.3	331.2	340.9	331.0	323.1	355.0	348.9	447.9																								
130	111.3	198.7	221.2	199.7	233.9	212.1	225.7	192.0	296.9	320.2	305.8	340.7	306.7	329.2	327.4	375.0	342.4	355.7	353.5	363.8	352.7	344.8	378.1	372.1	477.9																								
135	120.4	213.6	236.5	214.5	250.0	228.1	241.0	206.3	316.7	341.5	327.2	363.3	328.8	350.7	349.0	399.7	366.8	379.1	377.0	387.8	375.4	367.4	402.4	396.4	509.4																								
140	129.9	229.2	252.5	229.9	266.7	244.3	257.0	221.3	337.4	363.7	349.6	387.0	352.1	373.3	371.5	425.4	392.4	403.7	401.7	413.0	399.2	391.2	427.8	421.9	542.5																								
145	139.9	245.7	269.3	246.2	284.3	261.4	273.7	237.1	359.0	387.0	373.3	411.7	376.6	397.0	395.2	452.4	419.5	429.6	427.7	439.5	424.0	416.1	454.5	448.7	577.3																								
150	150.4	262.9	286.8	263.2	302.6	279.3	291.1	253.6	381.7	411.4	398.2	437.5	402.5	421.7	419.9	480.6	448.0	456.8	455.1	467.4	450.0	442.2	482.3	476.9	613.9																								

High Boiling Temperature

TEMP °F	123	245fa
35	19.5*	12.9*
40	18.2*	10.6*
45	16.6*	8.1*
50	15.0*	5.4*
55	13.2*	2.5*
60	11.2*	0.2
65	9.0*	2.0
70	6.6*	3.9
75	4.0*	5.9
80	1.2*	8.2
85	0.9	10.6
90	2.5	13.2
95	4.2	16.0
100	6.1	19.0
110	10.3	25.8
120	15.1	33.5
130	20.6	42.4

Low Boiling Temperature

TEMP °F	23	508B
-120	4.0*	2.9
-110	2.9	9.0
-100	9.0	16.6
-95	12.6	21.1
-90	16.7	26.0
-85	21.2	31.4
-80	26.2	37.4
-75	31.7	44.0
-70	37.7	51.1
-65	44.4	58.9
-60	51.7	67.4
-55	59.6	76.6
-50	68.2	86.6
-45	77.6	97.3
-40	87.8	108.9
-35	98.8	121.3
-30	110.6	134.6
-25	123.3	148.9
-20	137.0	164.2

Pressure: Psig
* inches mercury vacuum

Worldwide Sales Offices

For more information contact your
Honeywell Refrigerants representative

United States

Honeywell International
101 Columbia Road
Morristown, NJ 07962-1053
Phone: 800-631-8138
Fax: 973-455-6395

Latin America/Caribbean

Honeywell Chemicals Mexico
Constituyentes 900
Col. Lomas Atlas
C.P. 950, Mexico DF
Mexico
Phone: 52-55-5549-0303
Fax: 52-55-5544-9803

Canada

Honeywell Asca. Inc.
3333 Unity Drive
Mississauga, Ontario
L5L 3S6
Phone: 905-608-6325
Fax: 905-608-6327

Asia-Pacific

Honeywell (China) Co., Ltd.
No 430, Li Bing Road
Zhang Jiang Hi-Tech Park
Pudong New Area, Shanghai 201203
China
Phone: 86-21-2894-2000
Fax: 86-21-5855-2719

Honeywell Japan Inc.
New Pier Takeshiba
South Tower Building, 20th Floor
1-16-1 Kaigan, Minato-ku,
Tokyo 050022, Japan
Phone: 81-3-6730-7000
Fax: 81-3-6730-7221

Honeywell Chemicals, Korea
6F Janghakjaedan, B/D 44-1
Bangpo-Dong, Seocho-Ku
Seoul137040, Korea
Phone: 8-22-595-0204
Fax: 8-22-595-4964

Honeywell Specialty Chemicals
(Singapore) Pte. Ltd.
17 Changi Business Park Central 1
Honeywell Building
Singapore 486073
Phone: 65-6355-2828
Fax: 65-6783-2947

Honeywell Polymers (Australia) Pty.
Limited
Gr. Lvl. 71 Queens Road
Melbourne. 3002
Australia
Phone: 61-3-9529-1411
Fax: 61-3-9510-9837

Northern, Central, and Eastern Europe, Middle East and Africa

Honeywell Belgium NV
Haasrode Research Park
Grauwmeer 1
3001 Heverlee
Belgium
Phone: 32-16-391-209 and 391 216
Fax: 32-16-391-235

Southern Europe, Turkey and Israel

Honeywell Fluorine Products Italia Srl
V. Le Milanofiori EI
20090 Assago - MI - Italia
Phone: 39-02-892589600
Fax: 39-02-57500815

Customer Service

To place an order from anywhere in the
Continental United States, Hawaii and
the Caribbean:

Phone: 800-522-8001
Fax: 800-458-9073

Canada:

Phone: 800-553-9749
Fax: 800-553-9750

Northern and Central Europe

Phone: +32-16-391-209
Phone: +32-16-391-216
Fax: +32-16-391-235

Southern Europe, Middle East
and Africa

Phone: +39-02-9379-6777
ext. 24 / 25 and 26
Fax: +39-02-9379-6761

Outside these areas:

Phone: 1-973-455-6300
Fax: 1-973-455-2763



RESPONSIBLE CARE
OUR COMMITMENT TO SUSTAINABILITY

Disclaimer

All statements, information and data given herein are believed to be accurate and reliable but are presented without guaranty, warranty or responsibility of any kind, expressed or implied. Statements or suggestions concerning possible use of our products are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe any patent. The user should not assume that all safety measures are indicated, or that other measures may not be required.

Genetron®, AZ-20® and AZ-50® are registered trademarks of
Honeywell International Inc.
Performax is a trademark of Honeywell International, Inc.

G525-001
December 2011
Printed in U.S.A.
© 2011 Honeywell International Inc.